



Dimensions



All dimensions in [mm]

Detached electronics

Integrated electronics



1

Adapter plate *Optionally available with:*

- 1 Button
- Additional cable glands

2

Cable glands for customer interfaces

3

USB port
(detached / integrated electronics)

4

Display

5

Mounting holes 4x Ø5.2

Product description

The AMD 7.2 is a versatile and powerful electronics unit for controlling metal detection systems. It ensures precise detection of metallic foreign objects. It also supports reliable product separation and can be flexibly integrated into a very wide range of industrial applications.

Areas of application

The **AMD 7.2** electronics unit is designed for industrial use in **food and non-food applications**. It supports various conveying types, including **pressure conveying, suction conveying, free fall applications** as well as operation on **conveyor belts**. The possible **speed range extends from 0.001 m/s to 30 m/s**, which makes the AMD 7.2 suitable for processes with very low to very high conveying speeds. This allows for flexible use in a very wide variety of production and conveying environments.

Ambient conditions

Ambient temperature	- 10°C to +50°C
Storage / transport conditions	-10°C to +60°C
Relative humidity	0% to 95% (without condensation)

Electronic housing

Material	Stainless steel 1.4301 (AISI 304), sandblasted
Protection class	IP 66 - <i>different specifications on request</i>
Weight	6 kg

Functional characteristics

Operator interface	5.7" Touch display, colour (format 4/3)
Menu structure	3 Levels, 2 freely configurable hotkeys
Password protection	Individual user management
Status display	Display
Product memory / product management	Protected against power failure Parameter memory for 500 products
Log book / logging	20,000 Entries, protected against power failure
Multi-language capability	Multilingual user interface
Interfaces	Ethernet (RJ45), USB (type A)
Communication protocols	OPC UA, MODBUS TCP, WS FOOD, XML

Signal processing

Auto balance	Automatic adjustment to operating conditions
Active interference suppression	Multi-function filter system: Highly selective digital filter and dynamic response filter for interference-free operation
Frequency	Multiple frequencies, 3F(Metron CI)
Evaluation procedure	Basic Phase, Super Phase, Image Phase

Quality assurance

Functional test	Functional test via detector test Test of separation mechanism via software
Test piece management with teach functionality	Integrated
Event counter	Metal counter on the display (metal counter, detector test, separation unit test, external control, separation unit, product counter, AUTO test)
Type of data backup	microSD duplicated

Electrical properties

Operating voltage	100 V – 240 V AC, 50/60 Hz
Maximum power consumption	≤ 95 W
Mains connection	1.8 m cable with Schuko plug
Self-monitoring	Yes
Switching inputs	8 freely configurable inputs (24 V DC)
Switching outputs	4 Outputs (24 V DC), 2 potential-free contacts (250 V AC)

Versions

- ATEX (dust): Zone 21 | 22 (exterior)

Conformity

Optionally available:

- NRTL certification (61010-1)
- IEC certification (61010-1)

Options

- Power supply 24 V DC
- CON version (additional switching inputs and outputs)
- Country-specific power cable
- Electronics housing AISI 316L

Accessories

- WLAN module
- Signal combination for error status warning
- Display protective cover
- Metron signalling device protective cover
- Analogue input 4-20 mA
- Analogue output 0-10 V
- mesuEXPORT (automatic protocol export)
- mesuREMOTE (remote maintenance kit)
- mesuLINK (networking software)
- METRON RFID reader
- External reset "BUTTON"
- External reset "KEY"
- autoTEST system E (electrical)
- autoTEST system P (pneumatic)

© 2026 Mesutronic GmbH. All rights reserved.

This technical data sheet and all of the information, drawings and descriptions it contains are protected by copyright. Transfer to third parties, reproduction, or other use – even in part – is not permitted without the prior written consent of Mesutronic GmbH.

Technical changes and errors excepted.

Note:

If you require further product information that goes beyond the content of this technical data sheet and in particular concerns a specific use and the application of this product, please contact us.